

E35A Accessories

Name	Model	Outer Appearance	Specifications	Remarks
Pickup	E-DT-SM10A		5mmR, 90° conical diamond, 4mN	<ul style="list-style-type: none"> For ordinary measurements Standard accessory
Pickup	E-DT-SM11A		5mmR, 90° conical diamond, 4mN	<ul style="list-style-type: none"> For small holes Min. inner dia.: ϕ5mm
Pickup	E-DT-SM12A		5mmR, 90° conical diamond, 4mN	<ul style="list-style-type: none"> For extra small holes Min. inner dia.: ϕ3mm
Pickup	E-DT-SM13A		5mmR, 90° conical diamond, 4mN	<ul style="list-style-type: none"> For deep grooves Max. depth: 7mm
Standard piece	E-MC-S24B		Calibration surface: Approx. 3.1 μ mRa Actual measured value denoted	<ul style="list-style-type: none"> For magnification calibration and checking stylus Standard accessory
Adjustment tool (for rear measurements)	E-WJ-S64A			<ul style="list-style-type: none"> Standard accessory
Adjustment tool (for front measurements)	E-WJ-S80A			
Nose piece (for cylinders)	E-WJ-S85A			
Nose piece (for flat surfaces)	E-WJ-S88A			
Long hole extension adapter	DT57506			
Adapter for side direction measurements	DT57507			
Adapter for hole measurements	E-WJ-S86A			
Magnetic stand	E-ST-MAC			
Post mount holder	010 2050			
Post mount	E-CS-S26A			<ul style="list-style-type: none"> For ϕ6
RS-232C cable	E-SC-S248A		Compatible with 9-pin Windows PC connector	<ul style="list-style-type: none"> Provided with communication sample program